







Item	9PIN ON OFF Three Pole 220 Volt Rocker Switch With Solder Terminal
Function	ON OFF
Rating	16A 250VAC; 20A 125VAC
Contact Resistance	< 35MΩ
Insulation Resistance	500VDC 1000MΩ Minute
Dielectric Strength	1500VAC, 1 Minute
Operating Temperature	-25°C~+85°C
Electrical life	10000 CYCLES

### The Main Technology Performance

项目	Item	参数	Parameter
电路符号	Circuit		
额定电压、电压 Rated voltage Rated current		16 (6) 250V	
绝缘电阻 Insulated resistance		$\leq 100\text{M}\Omega$	
接触电阻 Contact resistance		$\leq 50\text{m}\Omega$	
介电强度 (kV/mm) Dielectric strength		$\geq 1500\text{V}/\text{AC}/55$	
热冲击寿命 Thermal shock life		$\geq 10000$ Cycles	
操作温度 Operating Temperature		$-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$	



11	零接触Zero line end	3	Brass HB2 5.0.8 黄铜	
10	接触片Contact piece	4	Brass HB2 5.0.6 黄铜	
9	内容	3	PBT 420S50 (白色)	
8	弹簧 Spring	3	Spring steel wire 弹簧线 5	
7	中端 Terminal	3	Brass HB2 5.0.8 黄铜	
6	边缘 Terminal	3	Brass HB2 5.0.8 黄铜	
5	接触点 Contact	3	AgCd1012/cu	
4	移动点 Moving piece	3	Brass HB2 5.0.6 黄铜	
3	动触点 Contact	3	AgCd1012/cu	
2	底座 Base	1	PA66(黑色)	
1	按钮 Button	3	PC(红色)	
NO.	名称 NAME	数量 QTY	材料 MATERIAL	表面处理 FINISHING

名称		型号:	
尺寸		料号:	
未注公差	线性	尺寸	比例: 1:1
尺寸	尺寸	版本: A1	视角: 90°
设计	审核	第二页	共 1 页
批准	生效时间	 东芝电子株式会社 TOSHIBA ELECTRON CO., LTD.	