

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[500-30B](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant

Wire Wrapping Wire

Kynar 1/0.25mm (30 AWG)

PRO-POWER
Quality Cables



Feature:

- Copper conductors are single silver plated, Kynar insulated.

Specifications:

105°C, no voltage rated, 30 AWG. Solid silver plated oxygen free copper.

Conductor:

Size	: 30 AWG, solid.
Material	: Silver plated oxygen free, high conductivity copper per ASTM-B 170 grade.
Plating	: Silver, 40 microinch minimum per ASTM-B-298.
Circular Mil Area	: 98 minimum.
D.C.R	: At 20°C (68°F) maximum 106.0Ω/M.
Elongation	: 20% before insulation.
Weight	: 0.0303 lbs./M.
Diameter	: 0.0100" nominal 0.0099" minimum.
Voltage Rating	: 300V.
Operating temperature	: -60°C to +105°C.

Insulation:

Material	: Kynar 460.
Minimum average wall	: 0.004".
Minimum any pt	: 0.003".
Colour	: As specified.
Diameter	: 0.0195" ±.001".
Spark Test	: 2000V ac RMS.
Weight	: 0.168lbs./M.
Total weight	: 0.47lbs./M.

PRO-POWER
Quality Cables

Wire Wrapping Wire

Kynar 1/0.25mm (30 AWG)

PRO-POWER
Quality Cables

Wire Wrapping Wire Rolls for Cut/Strip/Wrap Applications:

Wire Size		Insulation Diameter		Roll Size Meters	Green	Blue	Red	Black	White	Orange	Yellow	Violet
AWG	mm	Inches	mm									
30	0.25	0.0195	0.50	100	100-30G	100-30B	100-30R	100-30BK	100-30W	100-30O	100-30Y	100-30V
				500	500-30G	500-30B	500-30R	500-30BK	500-30W	-	500-30Y	-

Specification Table

Reel Length (m)	AWG	Colour	Part Number
100	30	Green	100-30G
		Blue	100-30B
		Red	100-30R
		Black	100-30BK
		White	100-30W
		Orange	100-30O
		Yellow	100-30Y
500		Blue	500-30B
		Green	500-30G
		White	500-30W
		Red	500-30R
		Yellow	500-30Y
		Black	500-30BK
		100	Violet

PRO-POWER
Quality Cables

Wire Wrapping Wire

Kynar 1/0.25mm (30 AWG)

PRO-POWER
Quality Cables

Notes:

International Sales Offices:



AUSTRALIA – Farnell InOne

Tel No: ++ 61 2 9645 8888
Fax No: ++ 61 2 9644 7898



FINLAND – Farnell InOne

Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411



NETHERLANDS – Farnell InOne

Tel No: ++ 31 30 241 7373
Fax No: ++ 31 30 241 7333



SWITZERLAND – Farnell InOne

Tel No: ++ 41 1 204 64 64
Fax No: ++ 41 1 204 64 54



AUSTRIA – Farnell InOne

Tel No: ++ 43 662 2180 680
Fax No: ++ 43 662 2180 670



FRANCE – Farnell InOne

Tel No: ++ 33 474 68 99 99
Fax No: ++ 33 474 68 99 90



NEW ZEALAND – Farnell InOne

Tel No: ++ 64 9 357 0646
Fax No: ++ 64 9 357 0656



UK – Farnell InOne

Tel No: ++ 44 8701 200 200
Fax No: ++ 44 8701 200 201



BELGIUM – Farnell InOne

Tel No: ++ 32 3 475 2810
Fax No: ++ 32 3 227 3648



GERMANY – Farnell InOne

Tel No: ++ 49 89 61 39 39 39
Fax No: ++ 49 89 613 59 01



NORWAY – Farnell InOne

Tel No: ++ 45 44 53 66 66
Fax No: ++ 45 44 53 66 02



UK – BuckHickman InOne

++ 44 8450 510 150
++ 44 8450 510 130



BRAZIL – Farnell-Newark InOne

Tel No: ++ 55 11 4066 9400
Fax No: ++ 55 11 4066 9410



HONG KONG – Farnell-Newark InOne

Tel No: ++ 852 2268 9888
Fax No: ++ 852 2268 9899



PORTUGAL – Farnell InOne

Tel No: ++ 34 93 475 8804
Fax No: ++ 34 93 474 5288



UK – CPC

++ 44 8701 202 530
++ 44 8701 202 531



CHINA – Farnell-Newark InOne

Tel No: ++86 10 6238 5152
Fax No: ++86 10 6238 5022



IRELAND – Farnell InOne

Tel No: ++ 353 1 830 9277
Fax No: ++ 353 1 830 9016



SINGAPORE – Farnell-Newark InOne

Tel No: ++ 65 6788 0200
Fax No: ++ 65 6788 0300



EXPORT – Farnell InOne

Tel No: ++ 44 8701 200 208
Fax No: ++ 44 8701 200 209

For enquiries from all other markets



DENMARK – Farnell InOne

Tel No: ++ 45 44 53 66 44
Fax No: ++ 45 44 53 66 06



ITALY – Farnell InOne

Tel No: ++ 39 02 93 995 200
Fax No: ++ 39 02 93 995 300



SPAIN – Farnell InOne

Tel No: ++ 34 93 475 8805
Fax No: ++ 34 93 474 5107



ESTONIA – Farnell InOne

Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411



MALAYSIA – Farnell-Newark InOne

Tel No: ++ 60 3 7873 8000
Fax No: ++ 60 3 7873 7000



SWEDEN – Farnell InOne

Tel No: ++ 46 8 730 50 00
Fax No: ++ 46 8 83 52 62

<http://www.farnellinone.com>

<http://www.buckhickmaninone.com>

<http://www.cpc.co.uk>

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-Power is the registered trademark of the Group. © Premier Farnell plc 2004.

PRO-POWER
Quality Cables

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[500-30B](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant