

SANYO

No.1777C

LA7620, 7621

Monolithic Linear IC

Color TV Video, Chroma, Deflection Circuit

The LA7620/7621 are small-sized multifunctional ICs containing the "video, chroma, deflection" circuit of NTSC color TV in the DIP30S (equivalent to the DIP22 package heretofore in use) of shrink type. Besides being small-sized, they have such features as greatly reduced number of parts and fewer adjustments required. The LA7620/7621 can be used in conjunction with the LA7520/7521 for "VIF.SIF" use and the LA7830/7831 for "vertical output" use to perform all color TV signal processings.

The LA7620 containing a peak clip circuit in the video circuit is well suited for use in small-sized sets. The LA7621 containing no peak clip circuit is well suited for use in large-sized sets.

Features


- . Small-sized package.
- . Minimum number of parts required.
- . Fewer adjustments required (Non-adjusting of functions shown below)
 - . Chroma VCO (APC)
 - . Horizontal OSC (H-Hold).
 - . Vertical OSC (V-Hold).
- . Multifunction.

Maximum Ratings at Ta=25°C

			unit
Maximum Supply Voltage	V _{16max}	14.0	V
Maximum Supply Current	I _{22max}	15.0	mA
Allowable Power Dissipation	P _{dmax}	1100	mW
Operating Temperature	T _{opg}	-20 to +85	°C
Storage Temperature	T _{stg}	-55 to +125	°C

Operating Conditions at Ta=25°C

			unit
Recommended Supply Voltage	V ₁₆	12.0	V
Recommended Supply Current	I ₂₂	10.0	mA
Operating Voltage Range		9.0 to 14.0	V
Operating Current Range		8.5 to 15.0	mA

Case Outline 3061-D30SIC
 (unit:mm)


Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO makes no information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringement of intellectual property rights or other rights of third parties.

Specifications and information herein are subject to change without notice.

SANYO Electric Co., Ltd. Semiconductor Overseas Marketing Div.
 Natsume Bldg., 18-6, 2-chome, Yushima, Bunkyo-ku, TOKYO 113 JAPAN

7310TS/N258TA/3265MW, TS No.1777-1/3

Operating Characteristics at $T_a=25^{\circ}\text{C}$, $V_{16}=12\text{V}$, $I_{22}=10\text{mA}$

[Chroma]

		min	typ	max	unit
ACC Amplitude Characteristic	ACC1	-3	0	3	dB
	ACC2	-7	0	+2	dB
ACC Phase Characteristic	ACC ϕ 1		0	± 3	deg
	ACC ϕ 2		0	± 7	deg
Maximum B-Y Demodulation Output	B-Y max	5.0			V _{pp}
Unicolor Amplitude Characteristic	ΔGU		17		dB
Tint Change Range	ΔT		110		deg
APC Pull-in Range	f_{APC}	± 300			
Color Difference Output DC Voltage	E_{RGB}	6.7	7.2	7.7	V
Color Difference DC Difference Voltage	$E_{\Delta\text{RGB}}$			± 300	mV
R-Y Relative Demodulation Angle	$\angle\text{R-Y/B-Y}$		104		deg
G-Y Relative Demodulation Angle	$\angle\text{G-Y/B-Y}$		-122		deg
R-Y Demodulation Ratio	R-Y/B-Y		0.9		
G-Y Demodulation Ratio	G-Y/B-Y		0.3		

[Video]

		min	typ	max	unit
Video Tone Control Characteristic	Gpmin	-5	-3	-1	dB
	Gpmax	12	15	18	dB
Video Voltage Gain	VG	12	15	18	dB
Contrast Variable Range	ΔGC		18		dB
Frequency Response	ΔGV $f=5\text{MHz}$	-5			dB

[Synchronization, Deflection]

		min	typ	max	unit
Synce Separation Input DC Level	$V_{s,s}$		9.3		V
Vertical Free-Running Frequency	f_V	$f_H/296.5$			Hz
Vertical Blanking Pulse Width	T_{BL}		19H		
Vertical Drive Stage Voltage Gain	VG		16		dB
Horizontal Free-Running Frequency	f_H		15.734		kHz
Horizontal Drive Output Pulse Width	T_H		24.5		us
Horizontal Synce Pull-in Range	f_{PULL}	± 400			Hz

For "Y-Chroma-Deflection" ICs for NTSC CTV use, the following Type Nos. are available. Select the IC most suited for your intended CTV set.

Type No.	Peak clip	DC Restoration	Quadratic differentiation circuit input polarity	Video tone		Remarks
				Soft	Sharp	
LA7620	○	70%	Positive	○	○	
LA7621	×	70%	Positive	○	○	
LA7625	○	100%	Positive	○	○	
LA7626	×	100%	Positive	○	○	
LA7629	×	100%	*Negative	×	○	Video band 10MHz

* : Inverting amp required

Equivalent Circuit Block Diagram and Sample Peripheral Circuit

